

HP10 MICROMatic



Part num.: IC0AKF214050652
Power (kvar) Ue=415V: 14
Power (kvar) Ue=400V: 12.6
Steps (kvar) Ue=400V: 1,8-3,6-7,2
Electrical steps nr.: 7
Disconnecter (A): 63
Icc (KA): 50 (Short-circuit withstand current conditioned by the upstream protective device)
PFC Controller: 5LGA
Weight (kg): 12
Dimensions (mm): WxDxH 460x260x480 (IP3X)

Ue	Un	Umax	f	THDIR%	THDIC%
400-415V	415V	455V	50 Hz	≤12%	≤50%

Generalities

Zinc-passivated metallic enclosure painted with epossidic dust paint, colour RAL 7035.
Auxiliary transformer to separate power and auxiliary circuit parts (110V).
Load-break switch with door interlock.
Special contactors with damping resistors to limit capacitors inrush current (AC6b).
FS17 450/750V self-extinguish cable according to EN 50525 - EN 50575 - EN50575/A1 standards.
Microprocessor Power Factor Correction relay.
CRM25 single phase self-healing metallized polypropylene capacitor with Un=415V rated voltage.

Keys:

Ue: rated operational voltage
Un: nominal voltage of the capacitor
Umax: maximum operating voltage
THDIR%: total harmonic distortion relatively to the current in the plant
THDC%: total harmonic distortion that capacitor withstands
THDVR%: total harmonic distortion relatively to the voltage in the plant
I250HZ%: percent current of 5th harmonic
Electrical steps nr.: represents the number of possible combinations of the steps

Technical Info

Rated operational voltage: Ue=400-415V
Rated frequency: 50Hz
Max current overload In (bank): 1.3xIn
Max current overload In (capacitors): 1,3xIn (continuous)
Max current overload In (capacitors): 2xIn (x 380s every 60 min.)
Max current overload In (capacitors): 3xIn (x 150s every 60 min.)
Max current overload In (capacitors): 4xIn (x 70s every 60 min.)
Max current overload In (capacitors): 5xIn (x 45s every 60 min.)
Max overload Vn (bank): 1.1xUe
Max overload Vn (capacitors): 3xUn (x 1 min.)
Insulation voltage: 690V
Temperature class (capacitors): -25/+55°C
Temperature class (bank): -5/+40°C
Discharge device: mounted on each bank
Installation: indoor
Service: continuous
Internal connection: delta
Operation devices: capacitors contactors (AC6b)
Total losses: ~ 2W/kvar
Inner surface finish: zinc passivation

ICAR by Ortea Next
Via dei Chiosi 21
20873 Cavenago Brianza MB - ITALY

Tel. +39 0295917800
www.icar.ortea.com
ortea@ortea.com



HP10 MICROMatic

