

VP20 MINImatic



Part num.: IF2ZLF275050652
Power (kvar) Un=460V: 75
Power (kvar) Ue=415V: 60
Power (kvar) Ue=400V: 56
Steps (kvar) Ue=400V: 5,6-11,2-16,8-22,4
Electrical steps nr.: 10
Disconnecter (A): 250
Icc (KA): 9
PFC Controller: 5LGA
Weight (kg): 94
Dimensions (mm): WxDxH 420x425x965 (IP3X)

Ue	Un	Umax	f	THDIR%	THDIC%
400-415V	460V	500V	50 Hz	≤27%	≤90%

Generalities

Zinc-passivated metallic enclosure painted with epossidic dust paint, colour RAL 7035.
 Auxiliary transformer to separate power and auxiliary circuit parts (110V).
 Load-break switch with door interlock.
 Special contactors with damping resistors to limit capacitors inrush current (AC6b).
 FS17 450/750V self-extinguish cable according to EN 50525 - EN 50575 - EN50575/A1 standards.
 Microprocessor Power Factor Correction relay.
 CRM25 single phase self-healing metallized polypropylene with increased thickness and Un=460V rated voltage.

Keys:

Ue: rated operational voltage
 Un: nominal voltage of the capacitor
 Umax: maximum operating voltage
 THDIR%: total harmonic distortion relatively to the current in the plant
 THDC%: total harmonic distortion that capacitor withstands
 THDVR%: total harmonic distortion relatively to the voltage in the plant
 I250HZ%: percent current of 5th harmonic
 Electrical steps nr.: represents the number of possible combinations of the steps

Technical Info

Rated operational voltage: Ue=400-415V
 Rated frequency: 50Hz
 Max current overload In (bank): 1.3xIn (continuous)
 Max current overload In (capacitors): 1.3xIn (continuous)
 Max current overload In (capacitors): 2xIn (x 500s every 60 min.)
 Max current overload In (capacitors): 3xIn (x 180s every 60 min.)
 Max current overload In (capacitors): 4xIn (x 90s every 60 min.)
 Max current overload In (capacitors): 5xIn (x 50s every 60 min.)
 Max overload In (bank): 1.1xUe
 Max overload In (capacitors): 3xUn (x 1 min.)
 Insulation voltage: 690V
 Temperature class (bank): -5/+40°C
 Temperature class (capacitors): -25/+70°C
 Discharge device: mounted on each bank
 Installation: indoor
 Service: continuous
 Internal connection: delta
 Total losses: ~ 2W/kvar
 Inner surface finish: zinc passivation

VP20 MINImatic

